



IDEM EMERGENCY STOP (E-STOP) SWITCHES ESL-SS

232003-GC
ESL-SS M20 '3NC 1NO' c/w GOLD CONTACTS

- Robust stainless steel emergency stop
- IP69K
- -25°C - 80°C
- 3 cable connection positions



Product description

Specifications

Annual usage	8 cycles per hour/24 hours per day/365 day
Approvals	EN60947-5-1, EN60947-5-5, EN62061, UL 508, ISO 13850, ISO 13849-1
Atex approved	No
Central Material	Stainless steel 316
Conduit entry	M20
Contact Type	EN60947-5-1 double break type Zb Snap Action up to 4NC (positive break) 2NO (Auxiliary)
Contacts	3NC 1NO
Integrated LED indication	No
IP Class	IP69K
Materials Contacts	Gold plated
Mechanical reliability B10d	2.5x10 ⁶ operations at 100mA load
Mounting	4 x M4

MTTFd	214 years
Number of poles	4
Operating temperature	-25°C +80°C
Operational rating	240v 3A
PFHd	<1.0 x 10 ⁻⁷
Rated insulation voltage	500V
Short circuit overload protection	Fuse externally 10A(FF)
Thermal current (Ith)	10
Withstand voltage	2500V

