

# DATASENSING

## **DATALOGIC IO-LINK MASTER CBX-8IOL**

## **IO-Link Connection Box**

CBX-8IOL-PROFINET 95ACC8190 PROFINET IO-Link master - 8 port M12 connection box



- 8 M12 IO-Link ports to PROFINET or ETHERNET IP
- IP67 Housing
- PLC access to IO-Link ISDU blocks
- Web server user interface

#### Product description

CBX-8IOL is a versatile active master exchange for IO-Link.

As a gateway with built-in OPC-UA technology, it combines the advantages of both IO-Link and Ethernet-IP, Profinet and Modbus in one and the same product series with two variants for suitable bus systems.

With CBX-8IOL, no PLC is integrated into the system, which reduces hardware and software costs.

IO-Link data can be sent by an IO-Link product directly to any SCADA or HMI software system.

The unique and integrated WEB server technology enables users to connect to IO-Link products with only one Ethernet-based device and use all commercial browsers, set up and read sensor parameters efficiently.

#### Specifications

Approvals	CE, cULus, FCC
Connection Thread	M12
Dimension (mm)	65 x 212 x 30
IP Class	IP67
LED indicator	Yes
Material	Plastic
Number Of Ports	8
Protocol	PROFINET
Weight	454