



IDEM GLHD WIRE SWITCH

141030A
GLHD 1/2NPT '4NC 2NO' LED 24V

- Up to 200 m for one switch
- 4 NC + 2 NO contacts
- 2 - color LED
- Integrated emergency button
- Available in the EX version



Product description

GLHD wire switch in an aluminum alloy housing, was created to protect long conveyors, with a range of up to 200 m per one switch. The 2-color LED, signaling the operation of the switch, is visible from a large distance. This switch, combined with the GLHL and GLHR models, provides a range of up to 250 m per one set.
The GLHD wire switches are equipped with 4 NC contacts and 2 NO contacts.

Specifications

Annual usage	8 cycles per hour/24 hours per day/365 days
Approvals	EN60947-5-5, ISO 13850, ISO 13849-1, EN62061, EN60947-5-1, UL 508, CE, cULus, TÜV
Central Material	Die cast metal
Conduit entry	4 x 1/2" NPT
Contact Type	EN60947-5-1 double break type Zb. Snap action up to 4NC (positive break) 2NO (auxiliary)
Contacts	4NC 2NO
Fittings	LED
Integrated emergency stop button	No
Integrated LED indication	Yes
IP Class	IP67
LED Display	Steady green/Flashing red
LED supply voltage	24Vdc

