

## MOLEX - MPM DIN FORM B INDUSTRIAL / DIN B MOULDED CABLE CONNECTOR

162N3N10021

Form Ind, 2P+Earth, H05, 1m Length, H12, Profile Gasket

- Fully overmoulded providing a high level of protection
- Quick and simple installation
- With or without LED and transient protection
- 11 mm or 10 mm contact distance EN175301-803 (DIN43650-B Industrial/-B)



### Product description

DIN Valve Connectors with moulded cable, IP65 rated. IP67 version available on request. Conforms to EN 175301-803.

### Specifications

<b>Cable length</b>	1000
<b>Circuit</b>	No circuit
<b>Color Cable</b>	Black
<b>Color Contact</b>	Black
<b>Color House</b>	Black
<b>Colour LED</b>	No LED
<b>Contact resistance</b>	≤15mΩ
<b>Cross-Section</b>	0.75
<b>Current max</b>	5
<b>IP Class</b>	IP65
<b>LED indicator</b>	No
<b>Material Cable</b>	PVC
<b>Materials Contacts</b>	Brass
<b>Number of poles</b>	2 + earth
<b>Packing Materials</b>	NBR
<b>Rated voltage</b>	250 V
<b>Screw and Gasket</b>	Profile NBR gasket & screw
<b>Temperature range from</b>	-40

