

MOLEX - MPM M8/M12-DIN A / DIN B INDUSTRIAL MOULDED CABLE CONNECTORS

F850B0P12M006

Cordset M12 str. male-DINB LED+VDR 60cm

- Fully overmoulded for better protection
- Quick and simple installation with M8 and M12
- With or without LED and transient protection
- EN175301-803 (DIN43650)-M8 / M12



Product description

DIN Valve Connectors with moulded cable, IP65 rated. IP67 version available on request.

Specifications

Cable length	0.6 m
Circuit	C4: LED & varistor
Color Cable	Black
Colour LED	Yellow
Connection male	M12
Connector	DINB Industry
Cross-Section	0.5
Current max	3
Head 1	DIN
IP Class	IP65
LED indicator	Yes
Material Cable	PUR/PVC
Temperature Range Flexible Use Of	-15
Temperature Range For Flexible Use	90
Temperature Range The Use Of	-40
Voltage AC / DC Max	24

3	ref. kábel
4	3
5	3
6	3
7	3
8	3
9	3
10	3
11	3
12	3
13	3
14	3
15	3
16	3
17	3
18	3
19	3
20	3
21	3
22	3
23	3
24	3
25	3
26	3
27	3
28	3
29	3
30	3
31	3
32	3
33	3
34	3
35	3
36	3
37	3
38	3
39	3
40	3
41	3
42	3
43	3
44	3
45	3
46	3
47	3
48	3
49	3
50	3
51	3
52	3
53	3
54	3
55	3
56	3
57	3
58	3
59	3
60	3
61	3
62	3
63	3
64	3
65	3
66	3
67	3
68	3
69	3
70	3
71	3
72	3
73	3
74	3
75	3
76	3
77	3
78	3
79	3
80	3
81	3
82	3
83	3
84	3
85	3
86	3
87	3
88	3
89	3
90	3
91	3
92	3
93	3
94	3
95	3
96	3
97	3
98	3
99	3
100	3

