## MOLEX - MPM DIN FORM A LOW HOUSING / HIGH HOUSING

C28200N0R

Form Industrial, 2P+Earth, Ext Thread, NBR Gask, IP67, Black

- With or without LED and transient protection
- Fibreglass-reinforced housing
- Turnable insert
- EN175301-803 (DIN43650)-A





## Product description

Standard internal thread DIN valve connector, IP65 rated. Available with different thread style, gaskets and circuitry. Conforms to EN 175301-803.

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the PG9 and PG11 internal thread connector cable range. Conforms to EN 175301-803.

## Specifications

Cable Diameter Max	9
Cable Diameter Min	4
Central Material	Polyamide
Circuit	No circuit
Color House	Black
Colour LED	No LED
Connector	DINA 43650
Cross-Section Max	1.5
Current max	16
IP Class	IP67
LED indicator	No
Manufacturer Part No	1212010001
Number of poles	2 + earth
Packing Materials	NBR
Rated voltage	250 V AC/300 V DC

Screw and Gasket	Integrated NBR Gasket & IP67 screw
Temperature range from	-40
Temperature range to	90

