

PH/ORP ELECTRODES

159001561

2725 - ORP electrode, flat tip, 3/4in NPT thread, use with 2751

+GF+

- Patented reference design for exceptional performance and prolonged life in harsh environments*
- PPS body for broad range of chemical compatibility
- Patented DryLoc® connector with gold plated contacts
- Special design allows for installation at any angle, even inverted or horizontal
- Quick temperature response



Product description


pH and ORP electrodes are general purpose sensors ideal for a wide range of applications. These feature a patented reference design and uses the unique foul-proof patented DryLoc® connector. The large area PE reference junction and pathway is constructed to increase the total reference effectiveness and ensures long service life.

The DryLoc® connector with corrosion resistant gold plated contacts readily connects the sensor to the mating 2751 pH/ORP Smart Sensor Electronics or the 2760 Preamplifier. The robust PPS threaded sensor body and choice of fl at pH, bulb pH, or fl at ORP sensing elements allows a broad range of chemical and mechanical compatibility for a wide variety of applications.

There are two optional pH sensing versions available, HF and LC. The HF version is for applications where traces of hydrofluoric acid (2% or less) will attack standard pH glass. The LC version can be used for low conductivity fluids 20 - 100 $\mu\text{S}/\text{cm}$ nominal and below 20 $\mu\text{S}/\text{cm}$ when mounted under controlled conditions.


The quick temperature response is available in either a Pt1000 or 3 K Ω temperature sensor and allows compatibility with all pH/ORP instruments. The 2724-2726 electrodes incorporate 3/4 inch NPT or ISO 7/1-R 3/4 threads for installing into GF standard pipe-tees. They can also be mounted directly into standard fittings, DN15 to DN100 (1/2 to 4 inch)

Dimensions




Mounting Angle

Models 2724-2726 may be mounted at any angle without affecting the performance.
*Avoid locations with air pockets and sediment.
When mounting in standard threaded fittings the electrode must be mounted horizontally to 60 degrees below horizontal position only.



Dimensions



Mounting Angle

Models 2724-2726 may be mounted at any angle without affecting the performance.
*Avoid locations with air pockets and sediment.
When mounting in standard threaded fittings the electrode must be mounted horizontally to 60 degrees below horizontal position only.

