GREISINGER WATERPROOF HANDHELD MEASURING DEVICE FOR PH/REDOX

GMH 5530

GMH-5530
Waterproof handheld measuring device without electrode



- Suitable for applications including, waters measuring - fishkeeping, aquafarming, drinking water monitoring, pharmaceutics, chemistry
- Connections for pH and Redox, Temperature, interface / supply
- Scope of supply: Device, battery, calibration protocol, manual
- Additional Display for pH-Electrode and Battery: Bar graph display

PRODUCT DESCRIPTION

SPECIFICATIONS

Additional information	Connections: pH, Redox: BNC-female connector, Temperature: 2 banana-jacks, Interface/supply: 4-pole bayonet connector
Battery Life	1000
Dimensions	160 x 86 x 37 mm
Display	two 4½ digit 7-segment, 15mm high
Measuring Range: pH	-2.000 … 16000 pH
Measuring Range: Redox	-2000.0 … 2000.0 mV
Measuring Range: rH	0.0 … 70.0 rH
Measuring Range: Temperature	-5.0 … 150°C
Operating temperature	-25 ... 50°C
Resolution	pH: ±0.005 pH, Redox: ± 0.05 %FS, Temperature: ±0.2°C, rH: ±0.1 rH
Type	pH handheld instrument
Weight	250