

# GREISINGER UNIVERSAL CONDUCTIVITY MEASURING DEVICES

## GLF 100, GLF 100 RW

GLF-100RW  
Conductivity meter for ultra-pure water

- Applications are varied but not limited to: Fresh and sea aquaristics, checking of pure and ultra-pure water
- With integrated temperature sensor
- Scope of supply: Device incl. measuring cell, battery, manual, calibration protocol (GLF 100),
- Automatic temperature compensation via integrated temperature sensor



### Product description

### Specifications

<b>Battery Life</b>	200
<b>Dimensions</b>	110 x 67 x 30 mm
<b>Display</b>	4½ digit LCD, 11mm high
<b>Measuring Range: Conductivity</b>	0.000 ... 2.000 µS/cm, 0.00 ... 20.00 µS/cm, 0.0 ... 100.0 µS/cm
<b>Measuring Range: Temperature</b>	-5.0 ... 100.0°C
<b>Operating temperature</b>	-25 ... 50°C
<b>Resolution</b>	Conductivity: typ. $\pm 1\%$ of m.v. $\pm 0.5\%$ FS, Temperature: $\pm 0.3^\circ\text{C}$
<b>Sensor</b>	Stainless steel electrode, applicability of the highest standard
<b>Type</b>	Conductivity meter
<b>Weight</b>	155