

## SCHNEIDER ELECTRIC ACTI9 DISTRIBUTION BOARDS MCB'S

SE10C110

1kq 1P 10A C Miniature Circuit Breaker

- Lockable in the ON or OFF position
- The operating frequency is 50Hz or 60Hz.
- It can be mounted on DIN rail for modular installation
- Its width is 2 pitches of 9mm.
- The dimensions are (W) 18mm x (H) 85mm x (D) 78.5mm.



### Product description

It complies with both industrial standard EN/IEC 60898-1 and residential standard EN/IEC 60947-2. This miniature circuit breaker protects circuits against short circuit and overload current. Its unique VisiTrip indicator reduces intervention time by showing the faulty circuit. Its VisiSafe green strip guarantees the physical opening of the contacts to allow downstream maintenance. Its fast closing mechanism independent of manual operation improves its service life. It has an electrical endurance going up to 10000 cycles and a mechanical endurance going up to 20000 cycles. The Ui rated insulation voltage is 500VAC. Its limitation class 3 (according to EN/IEC60898-1) improves downstream circuit protection cost. The product can be clipped on a DIN rail. Its width is 4 pitches of 9mm. Pollution degree is 3. The product colour is white (RAL9003). The dimensions are (W) 36mm x (H) 85mm x (D) 78.5mm. The weight is 0.25kg. According to IEC 60529 standard, the degree of protection is IP20 and IP40 in enclosure. The operating temperature is -35°C to 70°C. The storage temperature is -40°C to 85°C.