


## INSULATED BOOTLACE FERRULES 0.14MM<sup>2</sup> TO 4MM<sup>2</sup>

V30AE001662

Bootlace Ferrules 0.25sq-6mm Violet (Pack 500)

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### Product description

European manufactured, this range ensures a reliable crimp without splitting.

### Specifications

|                                   |                            |
|-----------------------------------|----------------------------|
| <b>Color</b>                      | Violet                     |
| <b>Conductor tube</b>             | Copper alloy               |
| <b>Contact surface</b>            | Galvanic tin-plated, shiny |
| <b>Country of origin</b>          | DE                         |
| <b>Cross Section Max</b>          | 0,25                       |
| <b>Diameter of collar</b>         | 1,8                        |
| <b>Diameter of tube</b>           | 0,85                       |
| <b>DIN 46228-1:1992</b>           | No                         |
| <b>DIN 46228-4:1990</b>           | Yes                        |
| <b>Length</b>                     | 10                         |
| <b>Length of tube</b>             | 6                          |
| <b>Operating temperature from</b> | -5                         |
| <b>Operating temperature to</b>   | 105                        |
| <b>Pack Size</b>                  | 500                        |

|                                   |                           |
|-----------------------------------|---------------------------|
| Plastic collar                    | Polypropylene-homopolymer |
| Rated wire cross section to (AWG) | 24                        |
| Standard                          | French Standard           |
| Stripping Length                  | 8                         |
| Tariff code                       | 85369010                  |
| Thickness of collar               | 0,25                      |
| Thickness of tube                 | 0,15                      |
| Weight                            | 0,06                      |

