DEFINOX - DPX AND DPAX

DE-AS076012100 DPX Butterfly valve SS-UH 3"



- · Quick installation and removal
- Can be used anywhere, many different types of gaskets
- Low pressure drop
- Product flow without media retention



Product description

We offer high quality butterfly valves that meet the strongest requirements of process technology, and are the ideal solution for food, brewery, cosmetic and pharmaceutical processes.

Technical advantages of DPX & DPAX butterfly valves:

- · From DN 25 to DN 150
- · Numerous end connections available: SMS DIN Clamp Between flange

Different Operating Systems:

- \cdot Stainless steel handle (right or left closing)
- · Multi-position handle (right or left closing)
- · Easy adjustment handle
- · Micrometric adjustment handle
- \cdot Normally open "NO", Normally closed "NC" or Double effect "DE" pneumatic actuator

Product benefits:


- · Reliable and economical technology
- · Quick installation and removal
- · Large range of gaskets allow this valve to be used anywhere
- · Low pressure drop
- · Product flow without media retention

With the option of: (to be ordered separately)

- · Mounting of pneumatic actuator
- \cdot Mounting the control top for controlling the valve
- · Mounting of handles in div. editions.

Specifications

Certificate	3.1 EN 10204
Connection	Weld ends
Description	Butterfly valve without handle
Design norm	SMS/DS



Disc Sealing Material	FKM
House	Aisi 316L
Housing	FKM
Internal Diameter	72
Outer Diameter	76
Surface Finish	0,8/1,2μm
Temperature range	0°C/120°C
Weight	2
Working Pressure Max	12



