



DEFINOX - SAMPLING VALVE - MICRO & MINI

Manual and Pneumatic

DE-PD006A6C3100

Micro valve 2 x 6/8 pipes, Pneumatic, FKM

- SIP or CIP
- Simple and safe solution for sampling
- Compact pneumatic actuator
- Fast and easy membrane replacement
- 3.1 EN10204 - EHEDG



Product description

PEX Test outlet valve

Specifications:

· DN 6/8 - DN 16/18

Materials:

· Body: stainless steel 1.4404 / 316L machined from solid piece

· Handle: white plastic or stainless steel 1.4301 / 304

· Membrane: FKM (black / green with spot) - WMQ (white) - EPDM (black) - PFA / EPDM (white - hard)

Connections:

· Clamp - Micro Ø25.4 mm or Mini Ø33.9 mm

Controls:

· Manual - PEX - Ergonomic handle

· Pneumatic

Surface:

· RA exterior = 0.8 µm

· RA inside = 0.8 µm standard (0.4 µm on request)

Operating conditions:

· Max. temperature: + 120 ° C

· Min. temperature: 0 ° C

· Max. working pressure: 10 bar

Specifications

Certificate	3.1 EN10204
Connection	Micro clamp
Description	Pneumatic
Flange size	Ø25.4mm
House	Aisi 316L/ 1.4404
Housing	FKM

Process Connection

2 x 6/8 pipes

Surface Finish

RA<0,8/1,2µm

