




DEFINOX - CHECK VALVE WITH CLAMP ENDS

DE-UU076A15100-R55
Check valve, 3", FKM

- Designed for a minimal pressure drop
- Vertical mounting for an improved seal
- Quick and easy installation
- Connection: Clamp
- Sealing types: PFA - FKM - EPDM - PTFE



Product description

Our products are of high quality and design that meet the strongest requirements of process technology and are the ideal solution for Food, Brewery, Cosmetics and Pharmaceutical processes!

Technical Advantages:

- 1/2" - DN 125
- Interior surface roughness $R_a = 0.8 \mu m$
- Vertical mounting for an improved seal and eliminate retention
- Fast and easy disassembly
- Connection: Welding ends
- Multiple packing types: PFA - FKM - EPDM.
- Approvals : 3A - ATEX - DESP - 3.1 - 2.1 - E1935 / 2004 - CE - REACH - ANIA

Specifications

| | |
|-------------------------------|----------------------|
| Certificate | 3.1 EN10204 |
| Connection | Clamp ends |
| Design norm | SMS |
| Exit | 90 Mbar |
| Flange size | Ø91mm |
| Housing | FKM |
| Internal Diameter | 72 |
| Material quality | 1.4404 |
| Outer Diameter | 76 |
| Surface Finish | $RA < 0,8/1,2 \mu m$ |
| Temperature range from | 0 |
| Temperature range to | 120 |

| | |
|-----------------------------|------|
| Weight | 2.31 |
| Working Pressure Max | 10 |