
DEFINOX - CHECK VALVE WITH CLAMP ENDS

DE-UU051A14100-R55 Check valve, 2", EPDM

- Designed for a minimal pressure drop
- · Vertical mounting for an improved seal
- Quick and easy installation
- Connection: Clamp
- Sealing types: PFA FKM EPDM PTFE



Product description

Our products are of high quality and design that meet the strongest requirements of process technology and are the ideal solution for Food, Brewery, Cosmetics and Pharmaceutical processes!

Tehcnical Advantages:

- · 1/2 "'- DN 125
- \cdot Interior surface roughness Ra = 0.8 μm
- \cdot Vertical mounting for an improved seal and eliminate retention
- · Fast and easy disassembly
- · Connection: Welding ends
- · Multiple packing types: PFA FKM EPDM.
- · Approvals .: 3A ATEX DESP 3.1 2.1 E1935 / 2004 CE REACH ANIA

Specifications

Certificate	3.1 EN10204
Connection	Clamp ends
Description	Plug with FKM
Design norm	SMS
Exit	90 Mbar
Flange size	Ø64mm
Housing	EPDM
Internal Diameter	48.5
Material quality	1.4404
Outer Diameter	51
Surface Finish	RA<0,8/1,2µm

Temperature range to	120
Weight	1.1
Working Pressure Max	10