



## DEFINOX - DCX 3 TANK OUTLET

pneumatic

DE-ED100A34101

DCX3 Tankoutlet, Lowering, Pneumatic, L-body,  
DN100, EPDM

- Leak tightness at high temperature and good resistance to chemical products
- Spherical body with large wall thickness ensures excellent resistance to expansion
- Can be used on a wide range of applications
- Complete interchangeability of sub-components
- Easy and fast maintenance thanks to the clamp assembly



### Product description

Definox DCX3 Tank outlet valve.

The ideal solution for Food, Brewery, Cosmetics, and Pharmaceutical processes.

The DCX3 is fitted as standard with a liquid PFA seal that ensures excellent cleaning of the valve.

Technical advantages:

- From DN 25 to DN 150
- Two versions: Raising or lowering plug
- PFA liquid seal, perfectly washable, ensures perfect leak tightness at high temperature and good resistance to chemical products
- Spherical body with thick walls ensures excellent resistance to expansion
- The plug can be supplied with an elastomer seal
- Pneumatic actuator, removable and easily adjustable: NO-NC-DE Double effect
- Possible use on a wide range of applications
- Complete interchangeability of sub-components
- Easy and fast maintenance thanks to the clamp assembly.

### Specifications

<b>Certificate</b>	3.1 EN10204
<b>Connection</b>	Weld ends
<b>Description</b>	Lowering plug
<b>Flange size</b>	Ø249mm
<b>Function</b>	Normally Closed (SPST)
<b>House</b>	L-body
<b>Housing</b>	EPDM
<b>Internal Diameter</b>	100
<b>Material quality</b>	1.4404

Max. pressure	7
Outer Diameter	104
Surface Finish	RA<0,8/1,2µm
Temperature range	-5°C/+140°C
Weight	47

