

## DEFINOX - DCX 3 TANK OUTLET

pneumatic

DE-ES025B11101  
DCX3 Tankoutlet, Hoisting, Pneumatic, L-body, 1",  
PFA/EPDM

- Leak tightness at high temperature and good resistance to chemical products
- Spherical body with large wall thickness ensures excellent resistance to expansion
- Can be used on a wide range of applications
- Complete interchangeability of sub-components
- Easy and fast maintenance thanks to the clamp assembly



### PRODUCT DESCRIPTION

Definox DCX3 Tank outlet valve.

The ideal solution for Food, Brewery, Cosmetics, and Pharmaceutical processes.

The DCX3 is fitted as standard with a liquid PFA seal that ensures excellent cleaning of the valve.

Technical advantages:

- From DN 25 to DN 150
- Two versions: Raising or lowering plug
- PFA liquid seal, perfectly washable, ensures perfect leak tightness at high temperature and good resistance to chemical products
- Spherical body with thick walls ensures excellent resistance to expansion
- The plug can be supplied with an elastomer seal
- Pneumatic actuator, removable and easily adjustable: NO-NC-DE Double effect
- Possible use on a wide range of applications
- Complete interchangeability of sub-components
- Easy and fast maintenance thanks to the clamp assembly.

### SPECIFICATIONS

Certificate	3.1 EN10204
Connection	Weld ends
Description	Hoisting plug
Flange size	Ø139mm
House	L-body
Housing	PFA/EPDM
Internal Diameter	22.6
Material quality	1.4404
Max. pressure	7
Outer Diameter	25

Surface Finish	RA<0,8/1,2μm
Temperature range	-5°C/+140°C
Weight	4.5

