# DEFINOX - DCX 3 TANK OUTLET

pneumatic

DE-ES025B11101
DCX3 Tankoutlet, Hoisting, Pneumatic, L-body, 1",
PFA/EPDM



- Leak tightness at high temperature and good resistance to chemical products
- Spherical body with large wall thickness ensures excellent resistance to expansion
- Can be used on a wide range of applications
- Complete interchangeability of sub-components
- Easy and fast maintenance thanks to the clamp assembly

## PRODUCT DESCRIPTION

Definox DCX3 Tank outlet valve.
The ideal solution for Food, Brewery, Cosmetics, and Pharmaceutical processes.
The DCX3 is fitted as standard with a liquid PFA seal that ensures excellent cleaning of the valve.
Technical advantages:
· From DN 25 to DN 150
· Two versions: Raising or lowering plug
· PFA liquid seal, perfectly washable, ensures perfect leak tightness at high temperature and good resistance to chemical products
· Spherical body with thick walls ensures excellent resistance to expansion
· The plug can be supplied with an elastomer seal
· Pneumatic actuator, removable and easily adjustable: NO-NC-DE Double effect
· Possible use on a wide range of applications
· Complete interchangeability of sub-components
· Easy and fast maintenance thanks to the clamp assembly.

## SPECIFICATIONS

| | |
|---|---|
| Certificate | 3.1 EN10204 |
| Connection | Weld ends |
| Description | Hoisting plug |
| Flange size | Ø139mm |
| House | L-body |
| Housing | PFA/EPDM |
| Internal Diameter | 22.6 |
| Material quality | 1.4404 |
| Max. pressure | 7 |
| Outer Diameter | 25 |

| | |
|---|---|
| Surface Finish | RA<0,8/1,2µm |
| Temperature range | -5°C/+140°C |
| Weight | 4.5 |




