



DEFINOX - DCX 3 DE LEAK-PROOF VALVE

Pneumatic

DE-DD050A14100 Seat valve DCX3 DE, L1-body, NC DN50 EPDM

- Perfect leak tightness at high temperature and good resistance to chemical products
- Excellent resistance to expansion
- · Leak indicator, for leaks between gaskets
- Able to absorb excess pressure under the plug
- · Quick installation and removal



Product description

Definox DCX3DE leak-proof valve

The DCXDE is a double sealing changeover valve which performs the same usual functions of a standard DCX3. It also enables a potential leak to be detected between the two isolated zones due to the chamber connected to the atomsphere. This is an alternative to mixproof leak chamber valves. This leak-proof valve meets the strongest requirements for process technology and is the ideal solution for Food, Brewery, Cosmetics, and Pharmaceutical Processes. The seat valve design offers a wide range of options and variants.

Technical advantages:

- · From DN 51 to DN 104
- · PFA liquid seal, perfectly washable, ensures perfect leak tightness at high temperature and good resistance to chemical products
- \cdot Spherical body with thick walls ensures excellent resistance to expansion
- · Different body configurations possible: + TL / LT / L
- · Numerous connections possible: SMS DIN Clamp
- · The plug can be supplied with an elastomer seal. This solution is reccomended for applications with charged liquids.
- · Pneumatic actuator- removable and easily adjustable: NO-NC-Double effect
- · Independent double valve system
- · Leak indicator, for leakage between gaskets
- \cdot Able to absorb excess pressure under the plug
- · The valve body is machine-made in a piece of solid steel that ensures excellent resistance to mechanical and thermal damage
- · Quick installation and removal
- \cdot Possible use on a wide range of applications
- · Complete interchangeability of sub-components
- \cdot Easy and fast maintenance thanks to the clamp assembly.

Specifications

Certificate	3.1 EN10204
Connection	Weld ends
Description	EHEDG design
Design norm	DIN
House	L1-body

Internal Diameter	50
Material Operator	Stainless steel AISI 304
Material quality	1.4404
Materials Seat Seal	EPDM
Outer Diameter	53
Pilot Pressure Max	7
Pilot Pressure Min	5.5
Surface Finish	RA<0,8/1,2µm
Temperature range	-5°C/+140°C
Weight	7.7
Working Pressure Max	8

