

DEFINOX - DCX 3 DE LEAK-PROOF VALVE

Pneumatic

DE-DD065A64100 Seat valve DCX3 DE, X2-body, NC DN65 EPDM

- Perfect leak tightness at high temperature and good resistance to chemical products
- · Excellent resistance to expansion
- · Leak indicator, for leaks between gaskets
- Able to absorb excess pressure under the plug
- · Quick installation and removal



Product description

Definox DCX3DE leak-proof valve

The DCXDE is a double sealing changeover valve which performs the same usual functions of a standard DCX3. It also enables a potential leak to be detected between the two isolated zones due to the chamber connected to the atomsphere. This is an alternative to mixproof leak chamber valves. This leak-proof valve meets the strongest requirements for process technology and is the ideal solution for Food, Brewery, Cosmetics, and Pharmaceutical Processes. The seat valve design offers a wide range of options and variants.

Technical advantages:

- · From DN 51 to DN 104
- · PFA liquid seal, perfectly washable, ensures perfect leak tightness at high temperature and good resistance to chemical products
- \cdot Spherical body with thick walls ensures excellent resistance to expansion
- \cdot Different body configurations possible: + TL / LT / L
- · Numerous connections possible: SMS DIN Clamp
- · The plug can be supplied with an elastomer seal. This solution is reccomended for applications with charged liquids.
- · Pneumatic actuator- removable and easily adjustable: NO-NC-Double effect
- · Independent double valve system
- · Leak indicator, for leakage between gaskets
- · Able to absorb excess pressure under the plug
- · The valve body is machine-made in a piece of solid steel that ensures excellent resistance to mechanical and thermal damage
- · Quick installation and removal
- \cdot Possible use on a wide range of applications
- · Complete interchangeability of sub-components
- \cdot Easy and fast maintenance thanks to the clamp assembly.

Specifications

| Certificate | 3.1 EN10204 |
|-------------|--------------|
| Connection | Weld ends |
| Description | EHEDG design |
| Design norm | DIN |
| House | X2-body |

| Internal Diameter | 66 |
|----------------------|--------------------------|
| Material Operator | Stainless steel AISI 304 |
| Material quality | 1.4404 |
| Materials Seat Seal | EPDM |
| Outer Diameter | 70 |
| Pilot Pressure Max | 7 |
| Pilot Pressure Min | 5.5 |
| Surface Finish | RA<0,8/1,2µm |
| Temperature range | -5°C/+140°C |
| Weight | 17.5 |
| Working Pressure Max | 8 |

