

## VALCO - CV SERIES FLOW INDICATOR

Sight glass/rotor

00.0006.0059.1

1,2..40 l/min H<sub>2</sub>O, G1/2F, Brass

- Ranges covering 0.6..80 l/min H<sub>2</sub>O
- Bidirectional
- Up to 25 bar max (depending on model)
- Brass connections



### Product description

The CV series flow indicator from Val.Co allows a visual inspection of the passage of liquids in hydraulic and water systems. The propeller is coloured for better visualization with opaque liquids and there is also an option for a blue propeller and an output.

### Specifications

<b>Colour of rotor</b>	Red
<b>Flow Range Max</b>	40
<b>Manufacturer Part No</b>	CV.015G.PSO.R
<b>Material of body</b>	Latene
<b>Material of connection</b>	Brass
<b>Material of glass tube</b>	Pyrex glass
<b>Material of rotor</b>	Polypropylene
<b>Material of seals</b>	NBR
<b>Max. pressure</b>	15
<b>Min flow rate for rotor (oil 40 Cst) l/min</b>	3
<b>Min flow rate for rotor (oil 41-150 Cst) l/min</b>	4
<b>Min flow rate for rotor (water) l/min</b>	1.2
<b>Pressure Drop</b>	0.3
<b>Process connection</b>	G1/2

