

## HONSBERG - FW1 SERIES FLOW SWITCH

### Piston

FW1-020GP011

Flow switch.plastic 1-11l/min,G3/4



- Switching Range 1..11 l/min H<sub>2</sub>O
- Water (Oil available on request)
- G $\frac{1}{4}$ " up to G1"
- Brass or POM Wetted Parts
- Max Pressure 10 bar

### Product description

Mechanical flow switch, for fluid media, with spring-supported piston and magnetic triggering of a reed switch. Robust construction in brass and POM

### Specifications

<b>Connection</b>	Internal thread, G $\frac{3}{4}$
<b>Contact Rating Max</b>	0.5
<b>Electrical Connection</b>	M12x1, 4-pole
<b>Flow Max l/min Double</b>	30
<b>Flow Range Max</b>	11
<b>Flow Range Min</b>	1
<b>Function</b>	Flask, reed contact, ending
<b>IP Class</b>	IP67
<b>Material of body</b>	POM
<b>Materials Spring</b>	Stainless steel 301
<b>Pressure drop</b>	0.2 bar at maximum flow
<b>Pressure Range Max</b>	10
<b>Temperature range of media to</b>	90
<b>Type of flow component</b>	Flow Switches
<b>Weight</b>	0.15
<b>Voltage AC max</b>	230

