HONSBERG - FLEX-F SERIES FLOW METER

Calorimetric

FLEX-F015HK029I



senseca

- No moving parts
- Wetted parts in stainless steel
- Simple installation of set point

Product description

Model Flex is a calorimetric flow sensor with analogue output signal and one switching point. It is equipped with LED indication and is simple to set via the magnetic tab.

Specifications

Accuracy	+/- 10% of the final value, but at least +/- 2 cm / s
Connection	External thread, G 1/2 "
Electrical Connection	Plug M12x1, 4-pole
Flow Range Max	150
Flow Range Min	1
Function	calorimetric
Hysteresis	0.04
IP Class	IP67
Load Max	100
	0.11
Material of body	Stainless steel 1.4305
Material of body Materials Clips	PA6.6
Materials Clips	PA6.6
Materials Clips Materials Wetted Parts	PA6.6 Stainless steel 316Ti
Materials Clips Materials Wetted Parts Output	PA6.6 Stainless steel 316Ti 4-20 mA
Materials Clips Materials Wetted Parts Output Power Consumption	PA6.6 Stainless steel 316Ti 4-20 mA 100
Materials Clips Materials Wetted Parts Output Power Consumption Pressure Range Max	PA6.6 Stainless steel 316Ti 4-20 mA 100 100





