HONSBERG - FLEX-F SERIES FLOW METER

Calorimetric

FLEX-F015HK029P



senseca

- No moving parts
- Wetted parts in stainless steel
- Simple installation of set point

Product description

Model Flex is a calorimetric flow sensor with analogue output signal and one switching point. It is equipped with LED indication and is simple to set via the magnetic tab.

Specifications

Accuracy	+/- 10% of the final value, but at least +/- 2 cm / s
Connection	External thread, G 1/2 "
Electrical Connection	Plug M12x1, 4-pole
Flow Range Max	150
Flow Range Min	1
Function	calorimetric
Hysteresis	0.04
IP Class	IP67
Load Max	100
Material of body	Stainless steel 1.4305
Material of body Materials Clips	Stainless steel 1.4305 PA6.6
·	
Materials Clips	PA6.6
Materials Clips Materials Wetted Parts	PA6.6 Stainless steel 316Ti
Materials Clips Materials Wetted Parts Output	PA6.6 Stainless steel 316Ti 4-20 mA + PNP transistor output
Materials Clips Materials Wetted Parts Output Power Consumption	PA6.6 Stainless steel 316Ti 4-20 mA + PNP transistor output 100
Materials Clips Materials Wetted Parts Output Power Consumption Pressure Range Max	PA6.6 Stainless steel 316Ti 4-20 mA + PNP transistor output 100 100





