

## HONSBERG - UK & UKV SERIES FLOW INDICATOR

Flow display with float

UKV-020GMW0003

Flow meter 1/8" w. valve, 0,2-3,0 l/h

- For liquids and air up to 6 bar
- Flow from 0.04 to 100 NI/min. air (0.2 to 220 l/h water)
- With or without needle valve



### Product description

Model UK is a variable area type flow meter. It is available in two different versions, with or without needle valve. It has been developed to measure liquids and gases in various forms.

### Special versions

- Special scales
- Connections in stainless steel
- Connections upwards and downwards (PVC)

### Specifications

<b>Accuracy</b>	± 5% of full setpoint
<b>Connection</b>	Internal thread, NPT 1/8 "
<b>Flow Max l/min Double</b>	0.1
<b>Flow Range Max</b>	0.05
<b>Flow Range Min</b>	0.003
<b>Function</b>	Flow indicator, swivel body, with needle valve
<b>Material of body</b>	Acrylic
<b>Material of connection</b>	Brass
<b>Material of seals</b>	NBR
<b>Materials Float</b>	Glass
<b>Pressure drop</b>	Approx. 0.1 bar at maximum flow

Pressure Range Max	6
Temperature range of media to	65
Type of flow component	Flowmeter
Weight	0.13

