

HONSBERG - UR1 SERIES FLOW SWITCH

Paddle

UR1-032GK

13,5..17,5l/minH₂O, G1¼F, SS

- Switching range 1,3..35 l/min
- Water (oils, gases and aggressive media available on request)
- G¾" up to G2"
- Brass or stainless steel wetted parts
- Max pressure 25 bar



Product description

The Honsberg UR1 is a simple flow switch which can easily be adjusted and also changed from normally open to normally closed. The flow switch works via a spring-supported paddle which moves according to the flow and when the specific flow is reached a magnetic reed switch is activated.

Special versions

- Plastic materials
- Weld/solder connection
- High volume OEM version
- Ex
- Switching ranges for oil or gas
- Special values
- High volume OEM version
- PVC (solder fitting)

Ordering information

- Specify direction of flow, medium, and switching range, UR1 or switching value UR2.
- For UR2 specify normally closed (n.c.) or normally open (n.o.).
- For oils, state viscosity, temperature and designation (e.g. ISO VG 68) (enquire about range).
- For gases, state pressure (relative or absolute), temperature and medium (e.g. air) (enquire about range).

Installation

- Include straight calming section of 5 x DN in inlet and outlet.
- Include a filter if the media is dirty (use magnetic filter for ferritic components).
- It must be ensured that the values given for voltage, current and power are not exceeded.
- When switched on, a load must be connected in series.
- The electrical details apply to ohmic loads. Capacitive, inductive and lamp loads must be operated using a protective circuit.
- Standard: horizontal inwards flow; switching head not recommended underneath; other installation positions are possible; the installation position affects the switching point and range.


Specifications

Specifications

Accuracy	±15% fs
Adjustable Switching Point L / Min Of Water	13,5..17,5 l/min
Connection	G1¼" female
Contact Rating Max	50
Electrical Connection	1.5m cable
Flow Max l/min Double	80
Function	Normally open or normally closed (SPST)
IP Class	IP65
Material of connection	Stainless steel
Materials Wetted Parts	Stainless steel, Hard ferrite, PTFE coating, FKM
Media	Water (oil, air and aggressive media on request)
Pressure drop	Approx. 0.01 bar at max. flow
Pressure Range Max	25
Temperature range of media from	20
Temperature range of media to	110
Weight	0.5
Voltage AC / DC Max	1
Voltage AC max	230

Adjustment

UR1 - loosen bolts, push the switching current tube into the desired position. Retighten the bolts.
Normally closed (n.c.) or normally open (n.o.) as per table "Technical data"




Dimensions and weights

G	Types	H	L	X	Weight kg
G ½	UR -010GM	62	50	10	UR1 0.35 UR2 0.35
	UR -010GK				0.40 0.40
G ¾ A	UR -015AM	60	12		0.35 0.30
	UR -015AP				0.15 0.15
G 1	UR -015GM	50	10		0.35 0.30
	UR -015GK				0.40 0.40
G 1¼	UR -020GM	63	12		0.35 0.35
	UR -020GK				
G 1	UR -025GM	87			0.40 0.40
	UR -025GK				0.45 0.45
G 1½	UR -032GM	91			0.40 0.40
	UR -032GK				0.50 0.50
G 1¾	UR -040GM	94			0.55 0.55
	UR -040GK				0.65 0.65
G 2	UR -050GM	103			0.80 0.75
	UR -050GK				0.95 0.95

Adjustment

UR1 - loosen bolts, push the switching current tube into the desired position. Retighten the bolts.
Normally closed (n.c.) or normally open (n.o.) as per table "Technical data"



G	Types	H	L	X	Weight kg
G ½	UR -010GM	62	50	10	UR1 0.35 UR2 0.35
	UR -010GK				0.40 0.40
G ¾ A	UR -015AM	60	12		0.35 0.30
	UR -015AP				0.15 0.15
G 1	UR -015GM	50	10		0.35 0.30
	UR -015GK				0.40 0.40
G 1¼	UR -020GM	63	12		0.35 0.35
	UR -020GK				
G 1	UR -025GM	87			0.40 0.40
	UR -025GK				0.45 0.45
G 1½	UR -032GM	91			0.40 0.40
	UR -032GK				0.50 0.50
G 1¾	UR -040GM	94			0.55 0.55
	UR -040GK				0.65 0.65
G 2	UR -050GM	103			0.80 0.75
	UR -050GK				0.95 0.95