ENCLOSURE LIGHTING - SL 025

SL 025

02527.0-00 Panel Lights Magnetic 230v

- Slim casing
- Electronic ballast
- Energy saving lamp
- Low energy fluorescent lamp





Product description

Both a magnetic bracket and IR sensor are available as options. If a magnetic bracket is chosen, installation is very simple and the lamp can be easily moved around in the cabinet to suit each situation. If you would also prefer an IR sensor, it only reacts when the door is opened, even if the door is transparent. Installation is facilitated even more in that a door switch is unnecessary.

Specifications

Activation	Switch
Approvals	CE, EAC, GS, RoHS, UL, UL E234324, VDE
Color	Light grey
Connection	3-pole terminal
Flamklass	UL94-V0
Frequenze	50/60 Hz
Height	40
Humidity Storage	<90% RH
IP Class	IP20
Length	345
Life span	10,000 Hrs
Light source	Low energy Fluorescent lamp
Luminance	900Lm
Material Plastic Housing	Plastic

Mounting	Screw fixing
Nominal voltage	230 V AC
Operating Humidity	< 90% RH
Operational Temperature	-20°C +50°C
Storage temperature	-45°C +70°C
Weight	0.4
Width	345
Voltage max	230 V ac
Voltage min	230 V ac

