

## ENCLOSURE LIGHTING LED 025 ECOLINE

### Ecoline

02540.1-11

Ecoline Panel Lamp 24-48V DC Screw Fixing + Switch

- LED long lifetime
- Externally switched version
- Wide AC/DC voltage range
- Quick connect spring terminals



#### Product description

LED025 ECOLINE is available in three different mounting options to suit different applications: Magnetic assembly, which can be mounted very quickly and can be moved around the cabinet if necessary. Screw mounting, for "traditional" mounting. Clip assembly, which is a type of screw mounting, but where the lighting can be angled and also easily moved as needed LED025 ECOLINE has the same luminance as a 95W bulb, but consumes only 5 W. LED025 ECOLINE is available with both 100-240 V AC and 90-110 V DC in one and the same unit, which makes it easy for both purchases and storage.

#### Specifications

<b>Activation</b>	Switch
<b>Approvals</b>	CE, cULus, EAC, RoHS, UL, UL E234324, VDE
<b>Color</b>	Transparent
<b>Connection</b>	2-pole dual cage clamp
<b>Height</b>	34
<b>Humidity Storage</b>	<90% RH
<b>IP Class</b>	IP20
<b>Length</b>	351
<b>Life span</b>	60,000h at +20°C
<b>Lifespan Electrical</b>	60 000h at +20 °C:ssa (+68 °F)
<b>Light source</b>	LED
<b>Luminance</b>	400Lm at 120°
<b>Material of body</b>	Plastic
<b>Mounting</b>	Screw fixing
<b>Nominal voltage</b>	24-48 V DC
<b>Operating Humidity</b>	< 90% RH

Operational Temperature	-30°C ... +60°C
Power Consumption	5
Protection Class	II (double insulated)
Storage temperature	-40°C ... +85°C
Weight	0.2
Width	52
Voltage max	60 V dc
Voltage min	20 V dc

