ENCLOSURE LIGHTING LED 025 ECOLINE

Ecoline

02540.1-11
Ecoline Panel Lamp 24-48V DC Screw Fixing + Switch

- LED long lifetime
- Externally switched version
- Wide AC/DC voltage range
- Quick connect spring terminals



Product description

LED025 ECOLINE is available in three different mounting options to suit different applications: Magnetic assembly, which can be mounted very quickly and can be moved around the cabinet if necessary. Screw mounting, for "traditional" mounting. Clip assembly, which is a type of screw mounting, but where the lighting can be angled and also easily moved as needed LED025 ECOLINE has the same luminance as a 95W bulb, but consumes only 5 W. LED025 ECOLINE is available with both 100-240 V AC and 90-110 V DC in one and the same unit, which makes it easy for both purchases and storage.

Specifications

Activation	Switch
Approvals	CE, cULus, EAC, RoHS, UL, UL E234324, VDE
Color	Transparent
Connection	2-pole dual cage clamp
Height	34
Humidity Storage	<90% RH
IP Class	IP20
Length	351
Life span	60,000h at +20°C
Lifespan Electrical	60 000h at +20 °C:ssa (+68 °F)
Light source	LED
Luminance	400Lm at 120°
Material of body	Plastic
Mounting	Screw fixing
Nominal voltage	24-48 V DC
Operating Humidity	< 90% RH
Operational Temperature	-30°C +60°C

Power Consumption	5
Protection Class	II (double insulated)
Storage temperature	-40°C +85°C
Weight	0.2
Width	52
Voltage max	60 V dc
Voltage min	20 V dc



