

## COMPRHEX INSULATORS

CPH2020

Insulator 22mm x 25mm x 6mm CPH20M6

- Red insulators in polyester
- Polyester reinforced with fiberglass
- Molded by compression
- Rated voltage 1000 V ac/1500 V dc
- Working temperature -40 to 130°C



### PRODUCT DESCRIPTION

The "stand off" insulator is used as an insulating support for active conductors to guarantee excellent electrical insulation capability; it can be used as a support for electrical devices, giving high mechanical resistance values, as well as a spacing and/or stiffening element of a system made of conductor bars (copper and/or aluminium).

The various heights, widths and sizes of the threaded inserts make it possible to select the most suitable reference for the specific installation.

The range offers two product types, both with high electrical insulation and mechanical resistance characteristics, obtained using different production processes and materials.

- COMPRHEX: red insulators and spacing columns made of polyester reinforced with fiberglass, molded by compression.
- ISO: black insulators and soacing columns made of polyamide reinforced with fiberglass, molded by injection.

Both ranges of have passed severe tests to check their mechanical and electrical resistance.

The values obtained during the tests are indicated in the relevant technical tables.

Tests are carried out in compliance with standards EN 60664-1 and EN 61439-1

### SPECIFICATIONS

Color	Red
Compressive strength	2900
d	18
E	6
F	9
Flexual strength	220
H	25
Insulation	Thermosetting Polyester reinforced with 20% fiberglass

Nominal torque	10
Operating temperature	-40 to 130°C
Rated voltage	1000 V AC/1500 V DC
Tensile strength	340
Thread size	M6
Weight	0.022

