



CYLINDRICAL FUSE HOLDERS

PMX, PMC, PMF, BAC

485120

PMX 10x38 fuse holder with Neutral feedthrough, 32A, 690 V



- Wide Range
- 25A to 125A
- Enclosed or open options
- UL Approved
- European manufacture

Product description

DF Electric have developed fuse holders which include the neutral pole within 1 module and the same applies to 3 pole +neutral fuse holders which come in a 3 module or 4 module option. Fuse holders offer a multitude of benefits for machine builders and panel builders, ensuring reliable and efficient circuit protection in their projects. Firstly, fuse holders provide a convenient and secure solution for installing and replacing fuses in machines and panels. The holders are designed to securely hold the fuses in place, preventing accidental disconnections and ensuring proper electrical contact. This ease of installation and replacement saves valuable time for machine builders and panel builders, allowing for quick maintenance and minimizing downtime. Furthermore, fuse holders offer enhanced safety for both the machines and the operators. In the event of an overcurrent or short circuit, the fuse holder acts as a barrier, isolating the fault and preventing further damage to the equipment. This protection not only safeguards the machines from potential electrical faults but also ensures the safety of the operators by reducing the risk of electrical hazards. Fuse holders provide machine builders and panel builders with the advantages of easy installation and replacement, enhanced safety, increased equipment longevity, and flexibility.

Specifications

| | |
|--------------------------------|--|
| Approvals | CSA, cRUS, IEC, Lloyd's, Rina |
| Country | ES |
| Indicator | No |
| IP Class | IP20 |
| Number of poles | 1 + N |
| Rated Current | 32 |
| Size | 10x38 |
| Standards | UL4248-1, CSA C22.2 N° 4248-1, IEC/EN60269-2, IEC/EN 60269-1 |
| Tariff code | 8536105090 |
| Weight | 117 |
| Width/number of modules | 1 |
| Voltage AC max | 690 |
| Voltage DC max | 750 |