

IDEM MULTIFUNCTIONAL UGB-KLT-SS ACCESS DEVICE

520001

UGB2-KLT-SS-RFID - Manual override



- Locking force F1Max = 3000N
- PL e Cat. 4
- An escape option
- Version for 2 or 4 buttons (lights, switches, e-stop)
- Built-in KLT circuit breaker with RFID coding

PRODUCT DESCRIPTION

UGB-KLT-SS is a multifunctional device that provides integrated protection and comprehensive access control. The product is intended for applications in which the operator has full access to a dangerous zone.

The switch is available in stainless steel version. In addition, the switch can have 2 or 4 buttons (lamps, switches) that can be freely configured. The UGB-KLT-SS multifunctional access device is coded with RFID, which ensures the highest level of interference immunity in accordance with the requirements of ISO14119.

SPECIFICATIONS

Approvals	ISO 13849-1, ISO 14119, EN60204-1, EN62061, EN60947-5-1, UL 508
Conduit entry	M20
Holding force (F1Max)	3000
Integrated LED indication	Yes
IP Class	IP65
Maximum approach / withdrawal speed	600
Mounting	4 x M6
Number of poles	2
Operating temperature	-25°C ... +40°C
PFHd	$4,77 \times 10^{-10}$
PL	e
Rated insulation voltage	600 V AC
SIL	3
Solenoid Voltage	24V dc
Travel for positive opening	10
Withstand voltage	2500 V AC