



# IDEM MULTIFUNCTIONAL UGB-KLT-SS ACCESS DEVICE

520002  
UGB2-KLT-SS-RFID-RR - Manual override

- Locking force F1Max = 3000N
- PL e Cat. 4
- An escape option
- Version for 2 or 4 buttons (lights, switches, e-stop)
- Built-in KLT circuit breaker with RFID coding



### Product description

UGB-KLT-SS is a multifunctional device that provides integrated protection and comprehensive access control. The product is intended for applications in which the operator has full access to a dangerous zone.

The switch is available in stainless steel version. In addition, the switch can have 2 or 4 buttons (lamps, switches) that can be freely configured. The UGB-KLT-SS multifunctional access device is coded with RFID, which ensures the highest level of interference immunity in accordance with the requirements of ISO14119.

### Specifications

Approvals	ISO 13849-1, ISO 14119, EN60204-1, EN62061, EN60947-5-1, UL 508
Central Material	Stainless steel 316
Conduit entry	M20
Head material	Stainless steel 316
Holding force (F1Max)	3000
Integrated LED indication	Yes
IP Class	IP65
Maximum approach / withdrawal speed	600
Mounting	4 x M6
Number of poles	2

<b>Operating temperature</b>	-25°C ... +40°C
<b>PFHd</b>	4,77 x 10 <sup>-10</sup>
<b>PL</b>	e
<b>Rated insulation voltage</b>	600 V AC
<b>SIL</b>	3
<b>Solenoid Voltage</b>	24V dc
<b>Travel for positive opening</b>	10
<b>Withstand voltage</b>	2500 V AC