



IDEM - MULTIFUNCTIONAL UGB-KLTM ACCESS DEVICE

525003
UGB2-KLTM-RFID - No Manual Override

- Locking force F1Max = 3000N
- PL e Cat. 4
- An escape option
- Version for 2 or 4 buttons (lights, switches, e-stop)
- Built-in KLTM circuit breaker with RFID coding



Product description

UGB-KLTM is a multifunctional device that provides integrated protection and comprehensive access control. The product is intended for applications in which the operator has full access to a dangerous zone.

The switch is available in a cast metal version. In addition, the switch can have 2 or 4 buttons (lamps, switches) that can be freely configured. The UGB-KLTM multifunctional access device is coded with RFID, which ensures the highest level of interference immunity in accordance with the requirements of ISO14119.

Specifications

Approvals	ISO 13849-1, ISO 14119, EN60204-1, EN62061, EN60947-5-1, UL 508
Central Material	Die cast metal
Conduit entry	M20
Head material	Stainless steel 316
Holding force (F1Max)	3000
Integrated LED indication	Yes
IP Class	IP65
Maximum approach / withdrawal speed	600
Mounting	4 x M5
Number of poles	2
Operating temperature	-25°C ... +40°C
PFHd	4,77 x 10 ⁻¹⁰

PL	e
Rated insulation voltage	600 V AC
SIL	3
Solenoid Voltage	24V dc
Travel for positive opening	10
Withstand voltage	2500 V AC

