IDEM - MULTIFUNCTIONAL UGB-KLTM ACCESS DEVICE

526003 UGB4-KLTM-RFID - No Manual Override

- Locking force F1Max = 3000N
- PL e Cat. 4
- An escape option
- Version for 2 or 4 buttons (lights, switches, e-stop)
- Built-in KLTM circuit breaker with RFID coding



Product description

UGB-KLTM is a multifunctional device that provides integrated protection and comprehensive access control. The product is intended for applications in which the operator has full access to a dangerous zone.

The switch is available in a cast metal version. In addition, the switch can have 2 or 4 buttons (lamps, switches) that can be freely configured. The UGB-KLTM multifunctional access device is coded with RFID, which ensures the highest level of interference immunity in accordance with the requirements of ISO14119.

Specifications

| Approvals | ISO 13849-1, ISO 14119, EN60204-1, EN62061, EN60947-5-1, UL 508 |
|-------------------------------------|---|
| Central Material | Die cast metal |
| Conduit entry | M20 |
| Head material | Stainless steel 316 |
| Holding force (F1Max) | 3000 |
| Integrated LED indication | Yes |
| IP Class | IP65 |
| Maximum approach / withdrawal speed | 600 |
| | |
| Mounting | 4 x M5 |
| Mounting Number of poles | 4 x M5 4 |
| | |

| PL | e |
|-----------------------------|-----------|
| Rated insulation voltage | 600 V AC |
| SIL | 3 |
| Solenoid Voltage | 24V dc |
| Travel for positive opening | 10 |
| Withstand voltage | 2500 V AC |

