

KP

KP 1/2NPT '3NC 1NO' SS head - HF actuator



-
- The image shows a red, rectangular safety interlock switch. It has a robust, industrial design with mounting holes and a circular port on the side. A label on the front provides the following information:
- IDEM** (brand name)
 - SAFETY INTERLOCK SWITCH** (function)
 - KORRA-KP** (model)
 - AC/DC 24V 3A 0W-100A** (voltage and current ratings)
 - IP67 EN60947-1-1** (protection and standard)
 - EN60947-1-1** (standard)
 - 9** (a small circular logo)
 - 1000 P.C.E.** (a small circular logo)
 - CE** (CE mark)
 - UL 94V-0** (UL rating)
 - 1000 P.C.E.** (a small circular logo)




The head can be rotated to give 4 actuator entry positions. For extra durability, Flexible Actuators and Stainless Steel head versions are available



- Positive Break Contacts to EN60947-5-1
- High Functional Safety to ISO13849-1
- 3 pole, 4 pole or Explosion Proof Contact Blocks
- Stainless Steel Head version available
- Connects to most Safety Relays to give up to PLe Cat.4
- Industry Standard Fitting: 52mm wide 98mm long 40mm fixing

Specifications

Actuator	Heavy duty flexible
Annual usage	8 cycles per day/24 hours per day/365 days
Approvals	ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508
Atex approved	No
Central Material	Polyester
Conduit entry	1/2" NPT
Contacts	3NC 1NO
Head material	Stainless steel 316
IP Class	IP67
Maximum approach / withdrawal speed	600
Mechanical reliability B10d	2.5 x 10 ⁶ operations at 100mA load
Mounting	2 x M5
MTTFd	356 years
Operating temperature	-25..80°C
PFHd	3.44 x 10 ⁻⁸
PL	e acc. ISO13849-1
Rated insulation voltage	500V ac
SIL	3 acc. EN62061
Thermal current (Ith)	5
Withstand voltage	2500V ac



Heavy Duty
Flexible
Stainless Steel

