


DOUBLE DECK TERMINALS - ZRKD 2.5MM²

ZRKD, ZSLD

3562.1
ZRKD 2,5 GN

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	UL, CSA, GL, CSA US, KEMA KUR, EAC
Color	Green
Connections	2 x 2
Contamination degree	3
Country of origin	CZ
Cross connect channels	2
Cross section single wire from	0.5
Cross section single wire to	4
Cross section stranded wire from	0.5
Cross section stranded wire to	4
Cross section stranded with ferrule from	0.5
Cross section stranded with ferrule to	2.5
Cross-Section	2.5
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
EAC test standard	TR ZU 004/2011
Flamklass	UL94-V0
GL test standard	IEC 60947-7-1:2009
Height TS 35/7.5	53

KEMA KEUR test standard	EN 60947-7-1:2009
Length	83.6
Number of levels	2
Number of test pick off options	4
Operating temperature from	-40
Operating temperature to	120
Overvoltage category	III
Pack Size	100
Plug gauge acc. EN 60 947-1	A3
Rated Current CSA	10
Rated current CSAus	10
Rated Current IEC	24
Rated Current To UL	10
Rated impulse voltage	6
Rated voltage CSAus	300
Rated Voltage IEC	500
Rated Voltage To UL	300
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	12
Stripping Length	10
Tariff code	85369010
UL test standard	UL 1059
Voltage CSA	300
Weight	12.8
Width	5.1

