

COMPACT TERMINALS FOR TS15/TS35 RAIL - ZSRK/ZSL 2.5MM²

ZSRK, ZSLN

3583.1
KDS-DE 2x 4-5 Grey Insert Max 5mmø

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



PRODUCT DESCRIPTION

SPECIFICATIONS

| | |
|--|---|
| Approvals | UL, CSA, GL, CSA US, cUL, KEMA KUR, EAC |
| Color | Green |
| Connections | 2 |
| Contamination degree | 3 |
| Country of origin | CZ |
| Cross connect channels | 1 |
| Cross section single wire from | 0.5 |
| Cross section single wire to | 4 |
| Cross section stranded wire from | 0.5 |
| Cross section stranded wire to | 4 |
| Cross section stranded with ferrule from | 0.5 |
| Cross section stranded with ferrule to | 2.5 |
| Cross-Section | 2.5 |
| CSA test standard | C22.2 No 158 |
| CSAus test standard | UL 1059 |
| cUL test standard | C22.2 No 158 |
| EAC test standard | TR ZU 004/2011 |
| Flamklass | UL94-V0 |
| GL test standard | IEC 60947-7-1:2009 |

| | |
|-------------------------------------|-------------------|
| Height TS 35/7.5 | 36.5 |
| KEMA KEUR test standard | EN 60947-7-1:2009 |
| Length | 43.5 |
| Load Current Max | 24 |
| Number of levels | 1 |
| Number of test pick off options | 2 |
| Operating temperature from | -40 |
| Operating temperature to | 120 |
| Overvoltage category | III |
| Pack Size | 100 |
| Plug gauge acc. EN 60 947-1 | A3 |
| Rated Current CSA | 20 |
| Rated current CSAus | 20 |
| Rated current cUL | 20 |
| Rated Current IEC | 24 |
| Rated Current To UL | 20 |
| Rated impulse voltage | 8 |
| Rated voltage CSAus | 300 |
| Rated voltage cUL | 300 |
| Rated Voltage IEC | 800 |
| Rated Voltage To UL | 300 |
| Rated wire cross section from (AWG) | 20 |
| Rated wire cross section to (AWG) | 12 |
| Stripping Length | 10 |
| Tariff code | 85369010 |
| UL test standard | UL 1059 |
| Voltage CSA | 300 |
| Weight | 5.4 |
| Width | 5.1 |



