

1213.2

SL 10/35 GNYE

SL 10/35 GNYE



M4

ERC



Nemko

C

Protective earth terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 10 mm, Colour: Green-yellow

Business data

Product description	Protective earth terminal
Packaging unit	80
Quantity unit	PC
Weight per piece (not including packaging)	32.8
Weight per piece (including packaging)	34.37
Unit of weight	G
Customs number	85369010
Country of origin	DE

1213.2

SL 10/35 GNYE

SL 10/35 GNYE

Technical Data

Dimensions

Length	56 mm
--------	-------

Width	10 mm
-------	-------

Height TS 35/7.5	47 mm
------------------	-------

Ratings

Rated cross-section	10 mm ²
---------------------	--------------------

Overvoltage category	III
----------------------	-----

Contamination degree	3
----------------------	---

1213.2

SL 10/35 GNYE

SL 10/35 GNYE

Technical Data

Connection data

Connection principle	Screw connection
Connection position	Lateral
Connections	2
Number of terminals per level	2
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.2 mm ²
Wire cross-section single core (rigid)/stranded, max.	10 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	10 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	10 mm ²
Wire cross-section AWG, min.	20
Wire cross-section AWG, max.	6
Stripping length	12 mm
Screw head	Slotted
Screw threading	M 4
Tightening torque, min.	1.2 Nm
Tightening torque, max.	2 Nm

1213.2

SL 10/35 GNYE

SL 10/35 GNYE

Technical Data

Materials

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

Further technical data

Mounting type	Mounting rail TS 35/7,5
---------------	-------------------------

Gauge plug acc. to EN 60 947-1	A5
--------------------------------	----

Number of cross-connection channels	1
-------------------------------------	---

Number of test pick-off options	1
---------------------------------	---

1213.2

SL 10/35 GNYE

SL 10/35 GNYE

Approvals

Standards and regulations

EAC approval	TR ZU 004/2011
--------------	----------------

EAC approval granted	✓
----------------------	---

Nemko approval	EN 60947-7-2
----------------	--------------

Nemko approval granted	✓
------------------------	---

cUL Recognized

cUL Recognized	C22.2 No 158
----------------	--------------

cUL Recognized	✓
----------------	---

cUL wire cross-section single-core (rigid) AWG, min.	20
--	----

cUL wire cross-section single-core (rigid) AWG, max.	6
--	---

cUL wire cross-section stranded AWG, min.	20
---	----

cUL wire cross-section stranded AWG, max.	6
---	---

cUL torque	16 Nm
------------	-------

cUL wire material	Cu
-------------------	----

1213.2

SL 10/35 GNYE

SL 10/35 GNYE

Approvals

KEMA KEUR approval

KEMA KEUR approval	EN 60947-7-2
KEMA KEUR approval granted	✓
KEMA wire cross-section single core (rigid), min.	0.2 mm ²
KEMA wire cross-section single-core (rigid), max.	10 mm ²
KEMA wire cross-section stranded, min.	0.2 mm ²
KEMA wire cross-section stranded, max.	10 mm ²
KEMA torque, min.	1.2 Nm
KEMA torque, max.	2 Nm

UL Recognized

UL Recognized	UL 1059
UL Recognized granted	✓
UL wire cross-section single-core (rigid) AWG, min.	20
UL wire cross-section single-core (rigid) AWG, max.	6
UL wire cross-section stranded AWG, min.	20
UL wire cross-section stranded AWG, max.	6
UL torque	16 Lb In
UL wire material	Cu
UL factory wiring	✓

1213.2

SL 10/35 GNYE

SL 10/35 GNYE

Approvals

UL Recognized

UL field wiring


✓

1213.2

SL 10/35 GNYE

SL 10/35 GNYE

Media



EAC



1213.2

SL 10/35 GNYE

SL 10/35 GNYE

Media




1213.2

SL 10/35 GNYE

SL 10/35 GNYE

Accessories

Quick-marking



Terminal marker / Pocket Maxicard, Length: 5 mm,
Width: 8 mm, Colour: White

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
9323.7	PMC SB 8/40 WH	4044211129231	400 PC

Screw driver



Screwdriver with bare blade, Colour: Black-grey

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1087.0	SDB 0,8x4,0	4044211014803	1 PC
