



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Multi-directional head
Product compatibility	XCKJ
Associated body	ZCKJ6H29 ZCKJD31H29 ZCKJD39H29 ZCKJ5H7 ZCKJD37H29 ZCKJD31 ZCKJ21 ZCKJ9H29 ZCKJ7 ZCKJ5 ZCKJ5H29 ZCKJ1H29 ZCKJ2H7 ZCKJ21H29 ZCKJ21H7 ZCKJ1 ZCKJD39 ZCKJ11H7 ZCKJ2 ZCKJ8 ZCKJ8H29 ZCKJD39H7 ZCKJD35 ZCKJ9H7 ZCKJD37 ZCKJ2H29 ZCKJ6H7 ZCKJ6 ZCKJ9 ZCKJ8H7 ZCKJD31H7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJD35H7
ZCKJ11
ZCKJ11H29
ZCKJ7H7
ZCKJD35H29
ZCKJ1H7
ZCKJD37H7
ZCKJ7H29

Movement of operating head	Multi-directional Rotary
Type of operator	Spring rod spring return
Type of approach	Multi-directional approach

Complementary

Switch actuation	By any moving part
Positive opening	Without
Head material	Metal

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.135 kg
Package 1 Height	0.380 dm
Package 1 width	0.380 dm
Package 1 Length	1.630 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------