



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ21H7 ZCKJD35H29 ZCKJD31H29 ZCKJ9H29 ZCKJ4H7 ZCKJ9H7 ZCKJ6H29 ZCKJ2H29 ZCKJ8H7 ZCKJD31H7 ZCKJ21H29 ZCKJD37H7 ZCKJ7H29 ZCKJ11H29 ZCKJ11 ZCKJ21 ZCKJ4H29 ZCKJ9 ZCKJ6 ZCKJD39 ZCKJD31 ZCKJD35H7 ZCKJ7 ZCKJD39H7 ZCKJD39H29 ZCKJD37 ZCKJ5H7 ZCKJ41H29 ZCKJ8 ZCKJD35 ZCKJ11H7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ41
 ZCKJ1H29
 ZCKJ4
 ZCKJ1
 ZCKJ5H29
 ZCKJ1H7
 ZCKJ7H7
 ZCKJ2H7
 ZCKJ41H7
 ZCKJ8H29
 ZCKJ2
 ZCKJD37H29
 ZCKJ5
 ZCKJ6H7

Movement of operating head	Linear
Type of operator	Roller plunger spring return metal
Type of approach	Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.152 kg
Package 1 Height	0.410 dm
Package 1 width	0.450 dm
Package 1 Length	0.870 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------