

Specifications



Eaton NITD32M50

Eaton Bussmann series low voltage british standard fuse, 32A, AC 415 V, V88/A1, 18 x 55 mm, gM, 32M50

General specifications

PRODUCT NAME	Eaton Bussmann series low voltage british standard fuse
CATALOG NUMBER	NITD32M50
MODEL CODE	32M50 415V AC BS88 FUSE
EAN	5027590504140
UPC	051712844390
PRODUCT LENGTH/DEPTH	57 mm
PRODUCT HEIGHT	18 mm
PRODUCT WIDTH	18 mm
PRODUCT WEIGHT	27.15 g
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	BS88 IEC 60269 EAC

EATON

Powering Business Worldwide

Product specifications

AMPERAGE RATING	32 A
FITTED WITH:	Offset bolted tags
FUSE SIZE	BS88/A1
CURRENT TYPE	AC
MOUNTING DIMENSION	M10
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	42.5 mm
BREAKING CAPACITY	80 kA
RATED SWITCHING CAPACITY	80 kA
MOTOR CURRENT RATING	32M50
RATED VOLTAGE AC	415 V
CLASS	Class gM
FUSE TYPE	NITD
UTILIZATION CATEGORY	gM (motor protection)
COLOR	None
INTERRUPT RATING	80 kAIC
FUSE INDICATOR	None
INSULATED METAL GRIPPING LUGS (IMGL)	No
WATT LOSSES	1.4 W
CONNECTION	Bolt-on
CONSTRUCTION	BS88/A1
CONSTRUCTION SIZE	A1
FUSE SHAPE	Offset slotted bolted tags
VOLTAGE TYPE	AC
SUITABLE FOR	CM32FC Camaster fuse holder
VOLTAGE RATING	415 V
TYPE	Fuse
APPLICATION	general industrial applications
FUSE SYSTEM (ACCORDING TO IEC 60269)	Fuse system E

Resources

CATALOGUES	eaton-bussmann-series-low-voltage-fuses-catalog-ca134002en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-low-voltage-british-standard-fuse-declaration-of-conformity-eu250456en.pdf eaton-low-voltage-british-standard-fuse-declaration-of-conformity-uk250939en.pdf
INSTALLATION VIDEOS	Video BS88 industrial fuse links
MCAD MODEL	eaton-iec-lv-fuses-mcad-3d-models-nitd-m-40-63a.stp
MULTIMEDIA	Eaton Bussmann - Red Spot fuse links
TECHNICAL DATA SHEETS	4106 NITD fuses

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

