



NMTR.E198865 Power Circuit and Motor-mounted Apparatus

Page Bottom

Power Circuit and Motor-mounted Apparatus

[See General Information for Power Circuit and Motor-mounted Apparatus](#)

PULS GMBH

E198865

Elektrastrasse 6
81925 Muenchen, GERMANY

Buffer units, open type Model(s) OPB020.1, SLV20.200, SLV20.X0X

UB10.KKX-XX (KK=input voltage, 22.5V thru 30V)

UB20.241-XX (If "XX" is blank the dash is omitted)

UBC10.KKX-XX (KK=input voltage, 22.5V thru 30V)

UC10.24Z-WX where Z can be 1 or 2, W can be blank or any number or C or S, X can be blank or any number

UF20.241, UF20.481

UF40.241-XX, where XX can be any character or number or blank, not safety relevant.

DC/DC converters, open type Model(s) CD5.121-X*, CD5.241*, CD5.241-L1-X*, CD5.241-L2-X*, CD5.241-S1-X*, CD5.242-X*, CD5.243-X*, SLAD4.100-X*

Industrial control equipment, miscellaneous apparatus, power supplies Model(s) PH1013-2440, PH1013-2840

QT40.999-70, QT40.999-72, PCS417.171, PCS417.381, PCS417.771

Industrial control equipment, protection and power distribution modules, built-in DC/DC (DIN-Rail), open type Model(s) PISA10.203206, PISA10.206210, PISA10.401, PISA10.402, PISA10.403, PISA10.404, PISA10.406, PISA10.410, PISA11.203206, PISA11.206212, PISA11.401, PISA11.402, PISA11.403, PISA11.404, PISA11.406, PISA11.410, PISA11.CLASS2

Industrial control equipment, switching power supplies, open type Model(s) OPS104.0, CS3.241-80

CS5.KKX-XX (b), CS5.241-80, CS5.315-80, CS5.316-80

DN1022, ML100.272-YY, ML100.xxx or alternatively AN328.xxx.xx

ML120.241-xx, ML120.CLASS2-xx, ML120.244-xx (g)

ML95.xxx, QS20.249-70 and QS20.249-72, QT40.24X-XX*, QT40.36X-XX*, QT40.48X-XX*, SD831, CS3.KKX-XX (b), SD832

Open Type, Industrial Control Equipment, switch mode power supply (DIN-Rail) Model(s) CS20.241-80 , CPS20.241-80, CS20.KKZ-WX, CPS20.KKZ-WX (!)

PIC120.241C-xx, PIC120.242C-xx, PIC120.241D-xx (k)

Rechargeable battery module, open type Model(s) UZK24.071, UZO24.071, UZK24.121, UZO24.121

Redundancy modules, open type Model(s) MLR02, MLR02.1XX, MLR02.5XX, MLY02, MLY02.1XX, MLY02.5XX, MLY10.241, SLR01, SLR01.5XX, SLR02, SLR02.5XX, SS832, YR2.DIODE-XX*, YR40.241-XX*, YR40.242-XX*, YR40.245-XX*, YR40.482-XX*, YR80.241-XX*, YR80.242-XX*, YRM2.DIODE-XX*

Sensor board for battery modules, open type Model(s) UZS24.100

Switching power supplies, open type Model(s) 2500P/1A3, 5000P/1A3, AC-1206, AC-1207, AC-1208, AC-1209, AC-1212, AC1213 (1-Phase), AC1216, AC1218, AC1224, AD-281, AN-277, AN-280, AN-283, AN-306, AN-322.XXX.XX, AN-327.XXX.XX, AN-328.XXX.XX, AP486.50X, CP10.121, CP10.241, CP10.241-S1, CP10.242, CP10.361, CP10.481, CP10.KKZ-WX (h)

CS10.KKX-XX* (KK=output voltage, 24 thru 28, 48 thru 52), CS10.241-80, CS10.311-80, CS10.315-80

CT10.24X-XX*, CT10.48X-XX*, CT10.241-80, CT10.311-80, CT10.315-80

CT5.KKX-XX (e), CT5.KKX-80 (f), DN1020, DN1021, DN2011, DN2012, DN2013, DN2014, DN2032, DN2033, DN2034, DN2035, DN2036, DN2114, DN2134, DPA144.XXX, DPA148.XXX, DPA154.XXX, DPA247.XXX, DPA248.XXX, DPS305.1, ML100.2XX-YY, ML100.6XX-YY

ML15.10K-XX* (K=output voltage, can be 0 (24-28V), 1 (5-5.5V) or 2 (12V))

ML15.KKX-XX* (K=output voltage), ML30.KK1-XX (b1), ML30.XXX, ML50.XXX, ML60.241-70, ML60.KK1-XX (i), ML60.KK2-XX (i), ML70.500, ML70.XXX, ML90.2XX-YY, ML90.6XX-YY, OPS105.2, OPS110.1, OPS110.2, OPS120.1, OPS305.1, OPS310.1, OPS320.1, OPS340.1, PS102, PU

101, QS10.DNET

QS10.XXY-ZZ, where XX represents the output voltage and can be 12 to 15 or 24 to 28 or 28 to 32 or 48 to 56, Y can be 1 to 4 or 6 to 9 for versions with 150 V DC input, for version with 300Vdc input Y is 5 or 1-D1, followed by -ZZ can be any alphanumeric character (not relied on safety) and QS10.DNET. Models may have suffix -C1 or -A1 which use coatings but not safety relevant.

QS20.249-JJ, QS20.KK1-XX, QS20.KK4-XX, QS20.KK5-XX, QS20.KK6-XX, QS3.241, QS40.244-XX*, QS40.484-XX*, QS40.KKZ-WX, QS5.241-WX (d), QS5.DNET, QT20.241-73, QT20.241-80

QT20.KKX-XX* (KK=output voltage, 24 thru 28, 36 thru 42 or 48 thru 55)

QTD20.241-XX*, RPS120 EEC or RPS120 EEC (CC) (d), RPS80 EEC, RPSXXX (RPS30), SD834, SL10.100, SL10.305, SL10.3XX, SL10.500, SL10.501, SL10.502, SL10.503, SL10.506, SL10.507, SL10.524, SL10.6XX, SL10.XXX, SL2.100, SL2.500, SL2.501, SL2.502, SL2.506, SL2.508, SL2.XXX, SL20.100, SL20.300, SL20.301, SL20.31X, SL20.501, SL20.502, SL20.503, SL20.506, SL20.600, SL20.601, SL20.602, SL20.606, SL20.61X, SL20.AXX, SL20.BXX, SL20.CXX, SL3.50X, SL30.300, SL30.301, SL30.500, SL30.506, SL30.507, SL30.512, SL30.AXX, SL30.BXX, SL4.YXX (a), SL40.300, SL40.XXX, SL5.YXX (a), SL5.ZXX (a), SLA3.10X, SLA4.1XX, SLA4.5XX, SLA5.XXX (1-Phase) (a), SLA8.1XX, SLA8.5XX, SLR.XXX, SLR10.100, SLR10.XXX, SLR2.XXX, SLR5.100, SLR5.XXX (1-Phase) (a), SVG-SEC-48-6, XT40.KK1-XX, XT40.KK2-XX

Investigated to ANSI/UL 508

Industrial control equipment, miscellaneous apparatus, power supplies Model(s) QT40.481-77; QT40.KKX-XX where: KK = Output voltage, 2 digit number 24 or 36 or 48; -XX = optional, X can be any character or number except -77, not safety relevant

Open Type, Industrial Control Equipment, switch mode power supply (DIN-Rail) Model(s) PIC240.241C-xx, PIC240.241D-xx, where xx can be any character or number or blank, not safety relevant.

PIC480.241C-XX, where XX can be any character or number or blank, not safety relevant

Redundancy modules, open type Model(s) PIRD20.241-XX*, YR2.1201-XX*, YR20.242-XX*, YR20.246-XX*

Switching power supplies, open type Model(s) CP20.241; CP20.241-S1; CP20.241-V1; CP20.241-V1-71; CP20.241-R1; CP20.241-R2; CP20.241-R3; CP20.241-R2-72

CP20.KKZ-WX-YY, where KK can be 12 up to 24 and denotes the rated output voltage; Z can be 1 and denotes version with 150 Vdc input; W and X can be any number, character or blank and defines product variants, which are covered in this report or additional product variants with minor, not safety relevant, deviations; YY can be any number, character or blank and defines product variants, which are covered in this report or additional product variants with minor, not safety relevant, deviations

(!) - KK represents the output voltage and may be 12 up to 15, 24 up to 28, 36 up to 42 and 48 up to 56 Vdc; For DC-supplied models KK may be 24 up to 28 and 48 up to 56 Vdc. Z may be 1; WX is optional, W can be blank or any number or 'C' or 'A' or 'S' or 'D'; "D" marks DC supplied models; X can be blank or any number and defines product variants, which are covered in this report or additional product variants with minor, not safety relevant difference.

(a) - X-stands for customer-specific versions, can be any character or number. not safety relevant. Y-stands for 1, 2, 4, 5 and single-phase versions and Z-stands for 3, 6, 7, 8 and three-phase versions.

(b) - Where KK=output voltage, is a two digit number from 24 thru 28; and X is optional, can be any character or number or blank, not safety relevant. Suffix -XX is optional and can be any character or number except for -80

(b1) - Where KK=output voltage, is a two digit number from 24 through 28; Suffix -XX is optional and can be any character or number.

(d) - W can be blank or any number or C or A, X can be blank or any number; not safety relevant. WX = "A1", WX = "C1" and RPS120 EEC (CC) represents a unit with conformal coated printed circuit boards. If W and X is blank the "-" is omitted

(e) - KK represents the output voltage and can be 30.5, 24-28 or 12-15 V, X can be any character or number, not safety relevant. Suffix -XX is optional and can be any character or number except for -80

(f) - KK represents the output voltage and can be 30.5, 24-28 or 12-15 V, X can be any character or number, not safety relevant.

(g) - Suffix "-xx" is optional and can be any character or number and is not safety relevant.

(h) - Where KK represents rated output voltage and can be 12, 24, 36 or 48; Z can be 1 or 2; WX is optional, W and X can be blank or any number or 'C' or 'A' or 'S' (not safety relevant), X can be blank or any number and defines additional product variants with minor, not safety relevant difference

(i) - Where KK=output voltage, is a two digit number from 12 through 15 and from 24 through 28; Suffix -XX is optional and can be any character or number except for -70

(k) - Where suffix '-XX' is optional and can be any letter or digit and is not safety relevant

* - X indicates a non safety relevant feature of the product and can be any alpha numerical character or be blank. Suffix -XX is optional and can be any character or number except for -80.

JJ - can be any character or number except 70 and 72, not safety relevant

Last Updated on 2017-11-27

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading

manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".