

universal busbar support (01485)



The picture may show a similar product.

Description

Part No.: **01485**000

universal busbar support

4-pole with internal screw holes

for busbars 12, 15, 20, 25, 30 x 5, 10

System

60Classic

Advantages of the product

With internal screw holes

can also be used as centre support

With the 4th pole, the width of the busbar can be set independent of L1, L2 and L3.

Product group 06

Subgroup 12

pack size 10
EAN 4021267014858

catalog page 2020 : 3.1

ECLASS 6.1 27400607
ECLASS 7.1 27400607
ETIM 4.0 EC001166
ETIM 5.0 EC001166

Approvals

Standards

IEC 61439-1:2011
UL 508

Approvals

CSA , UL , DNV GL , EAC



type number: 485
EAC Type: SB

UL file: E123577, UL category (for USA): NMTR2 <http://www.ul.com>
UL file: E123577, UL category (for Canada): NMTR8 <http://www.ul.com>
CSA file: 110285, CSA class: 3211-37 <http://directories.csa-international.org>
CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2011

Electrical data IEC

rated voltage (IEC) AC: 800 V

rated frequency (IEC): 50 / 60 Hz

rated isolation voltage U_i AC: 1000 V

rated surge voltage U_{imp} : 8 kV

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0.0 W.

(The power dissipation at full load would be 0.0 W.)

Kurzschlussfestigkeit:

Siehe Kurzschlussdiagramm im Bereich Download

Details UL

Standards

UL 508

Electrical data UL

rated voltage (UL) AC: 600 V

rated frequency (UL): 50 / 60 Hz

Mechanical data

W x H x D: 20 x 245 x 51

weight: 26.6 kg/100

poles: 3-pole+N

for busbars: 12, 15, 20, 25, 30 x 5, 10

Accessories



01131000

end cover

for busbar supports 01357 and 01485 (1x 01131 = 1 left + 1 right cover)